

GENERAC®

MOBILE

GLT4-M

GLT SERIES - LIGHTING TOWER



High illuminating
capacity



Long operating
time



Great
maneuverability



Wide
accessibility

- 4x 320W G5 LED
- Manual lifting system
- 2-cyl. diesel engine
- Site trailer



GLT4-M

Innovation comes through a careful management of space. The **GLT4-M lighting tower** combines all market requirements inside a very compact frame.

MAIN FEATURES

- 4x 320W G5 LED floodlights
- Vertical telescopic mast
- Manual lifting system with double handled winch
- Compact shape with “seagull-wing” doors for an easy access to the built-in generator
- Low-consumption engine (2 cylinders)
- Leaf spring site trailer (low speed) to reduce vibrations and absorb shocks during handling
- Long, foldable drawbar to optimize transport
- DSE 3110 digital controller
- Outlet electric socket (16A)
- Plastic fuel tank with liquid containment



Technical data

Minimum dimensions (L x W x H)	1656 x 1264 x 2433 mm
Maximum dimensions (L x W x H)	2756 x 2166 x 6777 mm
Dry weight	705 kg
Floodlights	4x 320W G5 LED
Luminous flux	211200 Lm
Illuminated area (1 lux min.)	7900 m²
Alternator (50 / 60 Hz)	3.5 kVA 230V / 4.2kVA 240V
Frequency	50 / 60 Hz
Engine speed (50 / 60 Hz)	1500 / 1800 RPM
Cylinder number	2
Engine cooling	Liquid
Average sound pressure level	60 dB(A) @ 7m
Running time*	225 h
Fuel tank capacity* (gross / net)	200 / 180 l
Liquid containment tank	√
16A single-phase inlet plug	Optional
16A single-phase outlet socket	√
Mast lifting system	Manual
Mast rotation	340°
Wind resistance	80 km/h

* Theoretical data to be confirmed